

Belvedere 5000 Hydronic Boiler

High output temperatures and extended burn time perfect for infloor heating.

The largest in our hydronic boiler range, the Belvedere 5000 is primarily designed for plant room installation, providing up to 50kw of heat. The Belvedere features a large symmetrical firebox which gives high output temperatures while extending the burn time between refuelling.

The Belvedere 5000 is often the best choice for infloor slab heating as its high output, spacious firebox and high capacity water jacket enables the initial temperature rise required for in-slab heating. It also has both manual and automatic airflow control, self-closing draught diverter, and temperature sensor grate and self-scooping ash pan with a separate firebox and ash pan doors, and separate damper and air controls - automatic and manual. The Belvedere 5000 utilises a standard 150mm (6") flue assembly.

All Dynamic Boilers contain mild steel waterways and require the addition of a water conditioner. We recommend the addition of "Thermablend" long life boiler conditioner and corrosion inhibitor to maintain the system in optimum working condition. If connecting a Dynamic Boiler to a domestic hot water service, a heat exchange tank system must be used.

The Belvedere 5000 can also be installed in a living room and a glass door option is available.

Heat Output: 50kw

Dimensions:

Height 1200mm

Width 585mm

Depth 710mm

Technical Specs:

For more detailed information on Dimensions and installation **click here**.

Complete System Option:

All Wiseliving heaters, cookers and boilers with hot water heating capability can be successfully combined with efficient, reliable, cost-effective solar hot water evacuated tube systems to provide domestic hot water.

Warranty:

All Wiseliving products are covered by our guaranteed warranty. For specifics on each product speak with our friendly staff.

Link to webpage: <https://www.wiseliving.com.au/belvedere-5000>